Product Overview Hydronic Underfloor Heating





Wired Room Controls

Wireless Room Controls

















		Danfoss Icon™ Dial 230V	Danfoss Icon™ Display 230V	Danfoss Icon™ Programmable 230V	Danfoss Icon™ Display 24V	Danfoss Icon™ Wireless Dial	Danfoss Icon™ Wireless Display Infrared available
Features	Energy saving	00	000	0000	00000	00000	00000
	Comfort level	Floor sensor not supported	Floor sensor not supported	Floor sensor supported	Floor sensor supported	Floor sensor not supported	Infrared floor sensor supported
	Advanced features				App Auto Supply C° control balancing control	App Auto Supply C° control	App Auto Supply C° control balancing control
	Cooling option			**	**	**	**
	Adaptive learning			~	~	~	~
	Switchable frames	Available for in-wall	Available for in-wall	Available for in-wall	Available for in-wall		
	Installation	On-wall In-wall	On-wall In-wall	On-wall In-wall	On-wall In-wall	On-wall	On-wall
	Master Controller fit	230V	230V	230V	24V	24V	24V

Product OverviewHydronic Underfloor Heating





Supply Temperature Controls Mechanical systems





		FHM-C1 Best with 230V system	Midi Shunt Danfoss Icon™ 230V included	
Features	Energy saving	000	000	
	Prefabrication (ready to go)	Incl. pump, temp. sensor and fittings	Incl. pump, temp. sensor, fittings and backplate. Needs only pipe connection. One circuit only	
	Plug and play installation	✓	✓	
	Control	Controlled by FTC temp. sensor	Controlled by FTC temp. sensor + Danfoss Icon™ 230V	

Basic Manifold



AdvancedManifold



		SSM (without flowmeter)	SSM-F (with flowmeter)
	Comfort level	a a	444
ures	Hydronic balancing	w w w	
Features	Pre-setting	+	++
	Integrated end section	✓	✓